

SPECIFICATIONS

FREQUENCY RESPONSE	20 Hz to 40 KHz +/- 1 dB (at send output) 30 Hz to 30 KHz +/- 1 dB (at speaker output, with processor threshold exceeded)
DISTORTION	<0.05%, 20 Hz to 20KHz 1 dB below rated output
SYSTEM SIGNAL TO NOISE RATIO	>80 dB @ 1 w, "A" WTD
POWER OUTPUT	125W/ch continuous average power, 4 or 8 Ω , both channels driven with THD < 1%
INPUT IMPEDANCE CHANNELS 1 - 4	Mic Input: 2 k Ω Line Input: 66 k Ω
INPUT IMPEDANCE STEREO CHANNELS	Phono: 78 k Ω 1/4": 78 k Ω
MAXIMUM INPUT LEVEL	Mic Input: -7 dBu Line Input: 30 dBu Stereo Input: 26 dBu
RETURN INPUT IMPEDANCE	47k Ω
FUSE TYPE	T6.3A, 250V
RETURN SENSITIVITY	0 dB for rated output power
PASSPORT SYSTEM	
Width	840 mm (33.7 in.)
Height	615 mm (24.2 in.)
Depth	300 mm (11.8 in.)
Weight	24 kgs (53 lbs)
SPEAKERS	
Width	340 mm (13.4 in.)
Height	610 mm (24.2 in.)
Depth	300 mm (11.8 in.)
Weight	6.8 kgs (15 lbs)
POWER TOWER	
Width	185 mm (7.3 in.)
Height	615 mm (24.2 in.)
Depth	300 mm (11.8 in.)
Weight	10.5 kgs (23 lbs)
Tower Footprint	350 x 300 mm (13.8 in. x 11.8 in.)
MICROPHONES	Dynamic Cardioid, balanced.
CABLES	XL -M to XL-F, 6 m. (20 feet)
SPEAKER CABLES	1/4 in. to 1/4 in., 9 m (30 feet)
	0 dBu is referenced to 0.775 volts rms